ADJ. ALUMINUM GANTRY CRANE WITH DUAL TIRE PNEUMATIC CASTERS - AHA-4-10-10-PNU APPROX WEIGHT: 460.12 lbs *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 120" 4 3/16" — 96 1/4" — REMOVABLE PIN 102 1/4" FOR HEIGHT **ADJUSTMENT** 112 1/8" MIN 142 1/8" MAX 104 1/8" MIN 134 1/8" MAX 3D VIEW 17 1/2" 5 7/8" TIRE 39 13/16" Ø 15 1/2" **WIDTH** 90 5/8" 57 9/16" -125 5/8" **DIMENSION TOLERANCE ± 1/4"** 73 1/16" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS SPECIAL FEATURES STANDARD FEATURES REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION MODEL NUMBER IS AHA-4-10-10-PNU NONE CAPACITY IS 4,000 LBS. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS **BASE WIDTH IS 73 1/16"** R UNITS REQUIRING APPROVAL DRAWINGS OR MAX OVERALL HEIGHT IS 142 1/8" MODIFIED ARE NON-RETURNABLE I-BEAM HEIGHT IS 8" [] As drawn [] As marked I-BEAM WIDTH IS 43/16" Signed: Date: OVERALL I-BEAM LENGTH IS 120" USABLE I-BEAM LENGTH IS 96 1/4" **Printed Name:** ADJUSTABLE UNDER I-BEAM HEIGHT LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING 104 1/8" MIN DISTRIBUTOR'S NAME: 134 1/8" MAX W.O.# X VESTIL MANUFACTURING HEIGHT IS ADJUSTABLE IN 6" INCREMENTS DRAWN BY: MTS (4) \emptyset 15 1/2" DUAL TIRE PNEUMATIC CASTERS DATE: 01/29/2021 SALES: X (SWIVEL WITH (4) LOCKING POSITIONS) -PNU MODELS ARE 12" TALLER THAN STANDARD reference: X SCALE: 1:38 FILE NAME: AHA UNITS OF THE SAME HEIGHT DESIGNATION QUOTED LEAD TIME: Y QUOTE # 28-007-460 **ALUMINUM CONSTRUCTION**