## **ALTERNATING TREAD STAIR - ATS-13-68** APPROX WEIGHT: 324.47 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\*ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE\*\*\* 23 5/8" -23 5/8" 20" 9 3/4" 0 TOP STEP - SCALE: 1:12 STEP - SCALE: 1:12 198" 12 1/4" 10 1/2" 7 7/16" STEP **HEIGHT SPACING** 128 1/4" 156 1/8" TOP STEP HEIGHT 34" 68°

70 1/8"

73 1/2"

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

PROJECT SIGN OFF

**SALES** 

ENG.

FAB.

**POWER** 

DIMENSION TO FRANCE ± 1/4

## MODEL NUMBER: ATS-13-68 CLIMB ANGLE: 68° NUMBER OF STEPS: 21 (INCLUDING TOP STEP) TOP STEP HEIGHT: 156 1/8" STEP HEIGHT SPACING: 7 7/16" HANDRAIL HEIGHT: 12 1/4" OVERALL HEIGHT: 198" OVERALL LENGTH: 73 1/2" OVERALL WIDTH: 23 1/2" CHAIN GATES AT TOP STEP RUBBER BUMPER STRIP FOR INTERNAL USE ONLY

STANDARD FEATURES

23 1/2"

9 1/8"

MAX CAPACITY IS 350 LBS TOUGH BAKED IN POWDER COATED YELLOW FINISH

SPECIAL FEATURES NONE

	DIMENSION TOLERANCE ± 1/4
A P P R O V	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.  ANY MODIFIED UNITS ARE NON-RETURNABLE  [ ] As drawn [ ] As marked
A	Signed:Date:
L	Printed Name:  LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING
DISTR	IBLITOR'S NAME:  P.O. #
אוכונו	IDUIUK SINAME: IEU.#

	_	Printed Name: LEAD TIME WILL START UP	ON RECEIF	PT OF SIGNED .	APPROVAL DRAWING
Y		BUTOR'S NAME:	P.O.# X		
	V	estil manufac	W.O.# X		
	DRAV	<sup>VN BY:</sup> B. WOOD		2/2009	SALES: X
	REFER	ENCE: X		SCALE: 1:35	FILE NAME:
	QUOI	TED LEAD TIME: X	QUOTE #	•	44-007-360