

65 3/4"

P

P

R

0

٧

Α

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

STANDARD FEATURES

MODEL NUMBER: ATS-7-56-HDG

9 1/8"

CLIMB ANGLE: 56°

23 1/2"

NUMBER OF STEPS: 12 (INCLUDING TOP STEP) TOP STEP HEIGHT: 84"

STEP HEIGHT SPACING: 7" HANDRAIL HEIGHT: 18 5/8" OVERALL HEIGHT: 126 3/8"

OVERALL LENGTH: 65 3/4"

OVERALL WIDTH: 23 1/2"

CHAIN GATES AT TOP STEP RUBBER BUMPER STRIP

MAX CAPACITY IS 350 LBS

HOT DIPPED GALVANIZED FINISH

HANDRAILS ARE TOUGH BAKED IN POWDER

COATED YELLOW FINISH

SPECIAL FEATURES

NONE

DIMENSION TOLERANCE ± 1/4" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION

COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE [] As drawn As marked

Signed: Date:

Printed Name:

| | | LEAD TIME WILL START UP | ON RECEIF | PT OF SIGNED . | APPROVAL DRAWING |
|----------------------------------|--------|-------------------------|-----------|----------------|------------------|
| | DISTRI | BUTOR'S NAME: | P.O.# X | | |
| , 20112 1111 (1 (O1) (O101(1) (O | | | | | W.O.# X |
| | DRAW | ^{/N BY:} TJH | DATE: 11/ | 18/2021 | SALES: X |
| , | REFER | ENCE: X | | SCALE: 1:30 | |
| | TOUG | ED LEAD TIME: X | QUOTE # | | 44-007-751 |