

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

SCALE: 1:30 FILE NAME:

SALES: X

Χ

44-007-752

STANDARD FEATURES

MODEL NUMBER: ATS-7-68-HDG

CLIMB ANGLE: 68°

NUMBER OF STEPS: 12 (INCLUDING TOP STEP) TOP STEP HEIGHT: 84"

STEP HEIGHT SPACING: 7"

HANDRAIL HEIGHT: 12 1/4" **OVERALL HEIGHT: 125 7/8"**

OVERALL LENGTH: 44 1/2"

OVERALL WIDTH: 23 1/2"

CHAIN GATES AT TOP STEP

RUBBER BUMPER STRIP

MAX CAPACITY IS 350 LBS HOT DIPPED GALVANIZED FINISH

HANDRAILS ARE TOUGH BAKED IN POWDER

COATED YELLOW FINISH

SPECIAL FEATURES

NONE

	DIMENSION TOLERANCE ± 1/4
A P P R O V	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE [] As drawn [] As marked
Ā	Signed:Date:
L	Printed Name: LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING
ISTRIBUTOR'S NAME: P.O.# X	
VESTIL MANUFACTURING W.O.# V	

QUOTE #

11/17/2021

TJH

REFERENCE: X

QUOTED LEAD TIME: X