## SPECIAL CARRIAGE MOUNTED COIL RAM - CCM-36-4-CL3 \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON HORIZONTAL CENTER OF GRAVITY: 12.77" STANDARD FEATURES VERTICAL CENTER OF GRAVITY: 8.79" EFFECTIVE THICKNESS: LESS THAN 1" MODEL NUMBER IS CCM-36-4-CL3 LOST LOAD: 134.47 lbs. CENTER OF **OVERALL WIDTH IS 12" OVERALL LENGTH IS 43 1/2"** GRAVITY Ø4 1/2" RAM O.D. **USABLE RAM LENGTH IS 36" OVERALL HEIGHT IS 24 1/2"** UNIFORM CAPACITY IS 3.000 LBS. 24 1/2" RAM O.D. IS 4 1/2" 12.77 FITS STANDARD CLASS III CARRIAGE 11" SPECIAL FEATURES 1 3/8" NONE 8.79 43 1/2' 11 1/2" 1/4" TYP. H4 5/8" DIMENSION TOLERANCE ± 1/4" I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION 22° Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO 20 1/4" **CONFIRM PRODUCT AND INSTALLATION** P COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ AND LOCAL REGULATIONS AND STANDARDS 1 1/4 R ALL SPECIAL UNITS ARE NON-RETURNABLE 0 1 As drawn [ ] As marked DETAIL A SCALE 1:10 Α Signed: LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME 5/8" 5/8" FOR INTERNAL USE ONL) W.O.# X PROJECT SIGN OFF \*\*NOTF\*\* VESTIL MANUFACTURING DUE TO VARIATIONS IN FORK TRUCK CARRIAGES **SALES** DRAWN BY: B.NOTHNAGEL DATE: 02/<u>04/2015</u> SALES: X PLEASE HAVE THE CUSTOMER VERIFY THAT THEIR ENG. CARRIAGE WILL CONFORM TO THE DIMENSIONS REFERENCE: X SCALE: 1:16 FILE NAME: SHOWN TO THE RIGHT, IF NOT, PLEASE HAVE THE FAB. CUSTOMER VERIFY DIMENSIONS B, T2, T3, & H4 TO QUOTED LEAD TIME: χ QUOTE # 08-007-279 BE ABLE TO QUOTE A SPECIAL BACKPLATE TO FIT. **POWER** Χ