SPECIAL CARRIAGE MOUNTED COIL RAM - CCM-48-4-CL3 *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON HORIZONTAL CENTER OF GRAVITY: 12.59" STANDARD FEATURES VERTICAL CENTER OF GRAVITY: 12.76" EFFECTIVE THICKNESS: LESS THAN 1" MODEL NUMBER IS CCM-48-4-CL3 LOST LOAD: 149.37 lbs. —— 48" —— CENTER OF **OVERALL WIDTH IS 12" OVERALL LENGTH IS 55 1/2" GRAVITY** Ø4 1/2" RAM O.D. **USABLE RAM LENGTH IS 48" OVERALL HEIGHT IS 24 1/2"** UNIFORM CAPACITY IS 3.000 LBS. 24 1/2" RAM O.D. IS 4 1/2" FITS STANDARD CLASS III CARRIAGE 12.59 11" SPECIAL FEATURES 1 3/8" NONE 12.76 55 1/2" 11 1/2" 1/4" TYP. H4 5/8" DIMENSION TOLERANCE ± 1/4" I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION 22° Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO 20 1/4" **CONFIRM PRODUCT AND INSTALLATION** P COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ AND LOCAL REGULATIONS AND STANDARDS 1 1/4 R ALL SPECIAL UNITS ARE NON-RETURNABLE 0 1 As drawn [] As marked DETAIL A SCALE 1:10 Α Signed: LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME 5/8" 5/8" FOR INTERNAL USE ONL) PROJECT SIGN OFF W.O.# X **NOTF** VESTIL MANUFACTURING DUE TO VARIATIONS IN FORK TRUCK CARRIAGES **SALES** DRAWN BY: B.NOTHNAGEL DATE: 02/<u>04/2015</u> SALES: X PLEASE HAVE THE CUSTOMER VERIFY THAT THEIR ENG. CARRIAGE WILL CONFORM TO THE DIMENSIONS REFERENCE: X SCALE: 1:16 FILE NAME: SHOWN TO THE RIGHT, IF NOT, PLEASE HAVE THE FAB. CUSTOMER VERIFY DIMENSIONS B, T2, T3, & H4 TO QUOTED LEAD TIME: Y QUOTE # 08-007-280 BE ABLE TO QUOTE A SPECIAL BACKPLATE TO FIT. **POWER** Χ