ELECTRIC HYDRAULIC SCISSOR LIFT TABLE, PARTIAL STAINLESS STEEL - EHLT-2448-1-43-PSS *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 24 3/8' **ELECTRIC TOEGUARDS (STOPS** 43" TABLE FROM LOWERING IF **RAISED** BUMPED) MEETS OSHA 1910.212 **HEIGHT IOWFRFD** ADJUSTABLE UPWARD HEIGHT TRAVEL LIMIT SWITCH CORD EXITS FRAME THIS END DIMENSION TOLERANCE ± 1/4" STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS MODEL NUMBER IS EHLT-2448-1-43-PSS REPRESENTED SATISFIES DESIGN AND DIMENSION PLATFORM WIDTH IS 24 3/8" REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION PLATFORM LENGTH IS 48 3/8" **OVERALL LENGTH IS 51"** PLATFORM RAISED HEIGHT IS 43" PLEASE CIRCLE SPECIFICATIONS COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE PLATFORM LOWERED HEIGHT IS 7" AND LOCAL REGULATIONS AND STANDARDS TABLE CAPACITY (EVENLY DISTRIBUTED) LOAD IS 1,000 LBS **POWER** UNITS REQUIRING APPROVAL DRAWINGS OR 0 MODIFIED ARE NON-RETURNABLE INTERNAL POWER UNIT MOTOR VOLTAGE 115 208 ٧ [] As drawn [] As marked CONTROL IS HANDHELD, 2 BUTTON, NEMA 4 DEDICATED CIRCUIT REQUIRED 60Hz PENDANT WITH MINIMUM 8' USABLE COIL CORD SAFETY MAINTENANCE PROPS, DISPLACEMENT STYLE CYLINDERS INSTALLED ROD DOWN EMERGENCY SAFETY STOP HYDRAULIC FUSES IN ALL CYLINDER. UNITS HAVE 2' TEST LEAD Signed: **MOTOR PHASE** SINGLE **THREE Printed Name:** DISTRIBUTOR'S NAME: CONTROL **HAND** AND PIG TAIL DECK TOLERANCE ± 1/2" FRAME AND DECK - MILL FINISH 304 STAINLESS STEEL GREASABLE PINS AND ROLLERS - 17-4 STAINLESS STEEL TABLE HEIGHT TOLERANCE ± 1/2" VESTIL MANUFACTURING W.O.# SCISSOR LEGSET - CARBON STEEL WITH DECK FLATNESS ± 1/4" TOUGH BAKED IN POWDER COATED WHITE FINISH DATE: 8/30/2017 SALES: X STAINLESS STEEL COMPONENTS HAVE AN UNPOLISHED (MILL) FINISH SCALE: 1:12 FILE NAME: SPECIAL FEATURES NONE QUOTED LEAD TIME: X QUOTE # 24-007-005-001