## ELECTRIC HYDRAULIC LIFT TABLE PORTABLE - EHLTP-3664-1-60-D2 \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON - 84 3/8" 36 3/8" **ELECTRIC TOEGUARDS** 60" (STOPS TABLE FROM **RAISED** LOWERING IF BUMPED) HEIGHT MEETS OSHA 1910.212 ADJUSTABLE UPWARD TRAVEL LIMIT SWITCH 36 11/16" 13" LOWERED HEIGHT (2) Ø 4" GLASS-FILLED-NYLON (2) Ø 4" GLASS-FILLED-NYLON STANDARD FEATURES RIGID CASTERS SWIVEL W/ BRAKE CASTERS MODEL NUMBER: EHLTP-3664-1-60-D2 DIMENSION TOLERANCE ± 1/4" **DECK WIDTH: 36 3/8"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS DECK LENGTH: 64 3/8" REPRESENTED SATISFIES DESIGN AND DIMENSION **OVERALL LENGTH: 84 3/8"** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. RAISED HEIGHT: 60" Ρ **LOWERED HEIGHT: 13"** MAX CAPACITY: 1,000 LBS. R UNITS REQUIRING APPROVAL DRAWINGS OR 0 TABLE CAPACITY (EVENLY DISTRIBUTED) MODIFIED ARE NON-RETURNABLE ٧ CONTROL IS HANDHELD 2 BUTTON, NEMÁ 4 [ ] As drawn [ ] As marked PENDANT WITH MINIMUM 8' USABLE COIL CORD INTERNAL POWER UNIT Signed: SAFETY MAINTENANCE PROPS, DISPLACEMENT **Printed Name:** STYLE CYLINDERS INSTALLED ROD DOWN LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING **EMERGENCY SAFETY STOP HYDRAULIC FUSES** DISTRIBUTOR'S NAME: IN ALL CYLINDERS W.O.# X VESTIL MANUFACTURING **DURABLE LIQUID PAINT BLUE FINISH** 12V DC WITH ONBOARD 115 CHARGER DRAWN BY: CRA

DATE: 02/24/2021

QUOTE #

Quoted lead time:  $_{
m Y}$ 

SALES: X

01-007-478

SCALE: 1:20 FILE NAME:

SPECIAL FEATURES

NONE