EFFICIENCY MASTER TILT TABLE - EM1-200-6050-6 APPROX WEIGHT: 801.81 lbs. *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 58" 53 1/2" -3D VIEW FOR REFERENCE RESTRAINT CHAIN 60" SLOT-LOCK BRACKET TILTED POSITION 12" **USABLE FORK POCKETS** 42 1/4" 45° 7 1/2" WIDE X 2 1/2" HIGH 24" 35 15/16" ON 30" CENTERS (LEVEL HEIGHT) 52 3/16" 45" **CORD EXITS** DIMENSION TOLERANCE ± 1/4" FRAME THIS END STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS MODEL NUMBER IS EM1-200-6050-6 REPRESENTED SATISFIES DESIGN AND DIMENSION MAX CAPACITY IS 6,000 LBS (EVENLY REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO DISTRIBUTED LOAD) Ρ CONFIRM PRODUCT AND INSTALLATION **DECK WIDTH IS 60"** COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ DECK LENGTH IS 50" AND LOCAL REGULATIONS AND STANDARDS R OVERALL LENGTH IS 58" UNITS REQUIRING APPROVAL DRAWINGS OR 0 DECK LEVEL HEIGHT IS 24" MODIFIED ARE NON-RETURNABLE ٧ **OVERALL HEIGHT TILTED IS 42 1/4"** [] As drawn [] As marked PLEASE CIRCLE SPECIFICATIONS: Α MAX TILT ANGLE IS 45° Signed: Date: SAFETY SLOT-LOCK RESTRAINT **POWER** AIR/OIL DC. CHAIN BRACKET MOTOR VOLTAGE 115 208 **Printed Name:** ALL STEEL CONSTRUCTION LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING **DURABLE LIQUID PAINT BLUE FINISH** DEDICATED CIRCUIT REQUIRED DISTRIBUTOR'S NAME: WARNING: CHECK STATE AND **MOTOR PHASE** SINGLE **THREE** LOCAL CODES VESTIL MANUFACTURING W.O.# CONTROL HAND **FOOT** CONTROL IS HANDHELD, 2 BUTTON, NEMA 4 DRAWN BY: MTS SALES: X PENDANT WITH MINIMUM 8' USABLE COIL CORD ~ ALL BATTERY CHARGERS ARE 115V AC ~ 10/12/2015 INTERNAL POWER UNIT reference: X BATTERY CHRG. ON-BOARD **REMOTE** SCALE: 1:32 FILE NAME: SPECIAL FEATURES YES CHRG. INDICATOR NO

* AVAILABLE AT ADDITIONAL COST

NONE

QUOTED LEAD TIME: $_{f Y}$

QUOTE #

Χ

03-007-073