TRIANGULAR SHAPED FORK EXTENSION - FE-4-54-T APPROX WEIGHT: 126 lbs *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 2 1/2" 5 1/8' 6 3/8' 54" **USABLE LENGTH** FORK EXTENSION MATERIAL THICKNESS IS 5/16" 57 1/8" **OVERALL LENGTH LEFT RIGHT** 4 3/4' (25/16")3/32" V.C.O.G. **CENTER OF GRAVITY** 4 1/2" 24 3/32" **USABLE WIDTH** H.C.O.G. **DIMENSION TOLERANCE ± 1/4"** STANDARD FEATURES SPECIAL FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION MODEL NUMBER IS FE-4-54-T NONE REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO FORK EXTENSION WIDTH: 5 1/8" Ρ CONFIRM PRODUCT AND INSTALLATION OVERALL WIDTH W/ LOOP: 6 3/8" COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. P USABLE WIDTH: 4 1/2" R OVERALL LENGTH: 57 1/8" UNITS REQUIRING APPROVAL DRAWINGS OR 0 **USABLE LENGTH: 54'** MODIFIED ARE NON-RETURNABLE FITS 4" WIDE x 2" MAX. THICKNESS FORK V As drawn [] As marked SOLID STEEL CONSTRUCTION TOUGH BAKED IN POWDER COATED YELLOW FINISH Signed: Date: APPROX. WEIGHT / LOST LOAD = 126 LBS. PER PAIR MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" **Printed Name:** CAPACITY = 4,000 LBS. PER PAIR, EVENLY DISTRIBUTED LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING FORK EXTENSIONS DO NOT INCREASE THE LOAD DISTRIBUTOR'S NAME: CENTER OF EXISTING FORK TRUCK NEVER EXCEED LOAD CENTER RATING PER FORK VESTIL MANUFACTURING W.O.#

NEVER EXCEED LOAD CENTER RATING PER FORK
TRUCK MANUFACTURER'S GUIDELINES

DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL
EXCEED FORK TRUCK MANUFACTURER'S LOAD
CENTER RATING
FORK EXTENSIONS MUST NOT EXCEED 150% OF
ORIGINAL FORK LENGTH

ORIGINAL FORK LENGTH

OSSINDORS NAME:

VESTIL MANUFACTURING

W.O.#

X

WO.#

X

DRAWN BY:
X

REFERENCE:
X

QUOTED LEAD TIME:
X

QUOT