## APPROX WEIGHT: 99.21 lbs. FORK EXTENSIONS, PIN STYLE - FE-4-63-P DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 66 5/8" **OVERALL LENGTH** 63" **USABLE LENGTH** 9 1/2" FORK CLEARANCE 2 1/2" 5 1/8"+/- 1/8" **PIN STYLE** LOCK (25/16") 3/4" 29 7/16" (F=F ×ô¢ 0 0 CENTER OF GRAVITY 4 1/2" 2" STANDARD FEATURES USABLE FORK EXTENSION MATERIAL WIDTH MODEL NUMBER: FE-4-63-P THICKNESS IS 5/16" SPECIAL FEATURES FORK EXTENSION WIDTH: 5 1/8" **DIMENSION TOLERANCE ± 1/4" OVERALL WIDTH W/ RETAINING PIN: 9 1/2"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS NONE USABLE WIDTH: 4 1/2" REPRESENTED SATISFIES DESIGN AND DIMENSION Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION OVERALL LENGTH: 66 5/8" Ρ **USABLE LENGTH: 63"** Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE DESIGNED TO FIT 4" WIDE x 2" THICKNESS FORK AND LOCAL REGULATIONS AND STANDARDS R SOLID STEEL CONSTRUCTION UNITS REQUIRING APPROVAL DRAWINGS OR 0 TOUGH BAKED IN POWDER COATED YELLOW FINISH MODIFIED ARE NON-RETURNABLE V [] As marked [] As drawn APPROX. WEIGHT / LOST LOAD = 99.21 LBS. PER PAIR Α MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" Date: Signed: CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED FORK EXTENSIONS DO NOT INCREASE THE LOAD CENTER OF EXISTING FORK TRUCK. NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES. DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD

CENTER RATING. FORK EXTENSIONS MUST NOT EXCEED 150% **ORIGINAL FORK LENGTH** 

	Printed Name:			
LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING				
DISTRIBUTOR'S NAME:				P.O.# X
VESTIL MANUFACTURING				W.O.# X
DRAWN BY: DEC		5/23/16		<sup>SALES:</sup> X
REFER	ENCE: X		SCALE: 1:12	FILE NAME:
QUO'	ED LEAD TIME: X	QUOTE # X		08-007-343