APPROX WEIGHT: 150.06 lbs. FORK EXTENSIONS- FE-4-90-RS DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON - 5 1/8"±1/8" 2 1/2" 4 6 3/8" 78" USABLE LENGTH 93 1/8" FORK EXTENSION MATERIAL **OVERALL LENGTH** THICKNESS IS 5/16" Ø 5/8'' 9/16"-(25/16") 37/8 0 0 0 4 1/2" CENTER OF GRAVITY -USABLE STANDARD FEATURES WIDTH MODEL NUMBER IS FE-4-90-RS SPECIAL FEATURES DIMENSION TOLERANCE ± 1/4" **OVERALL WIDTH** IS 5 1/8"±1/8" NONE I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS OVERALL WIDTH W/LOOP IS 63/8" REPRESENTED SATISFIES DESIGN AND DIMENSION **USABLE WIDTH IS 4 1/2"** A REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO **OVERALL LENGTH** IS 93 1/8" **USABLE LENGTH** IS 78" **OVERALL HEIGHT IS 37/8"** FITS 4" WIDE x 2" MAX. THICKNESS FORK SOLID STEEL CONSTRUCTION

SOLID STEEL CONSTRUCTION TOUGH BAKED IN POWDER COATED YELLOW FINISH APPROX. WEIGHT / LOST LOAD = 150.06 LBS.PER PAIR MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED FORK EXTENSIONS DO NOT INCREASE THE LOAD CENTER OF EXISTING FORK TRUCK. NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES. DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL EXCEED FORK TRUCK MANUFACTURER'S LOAD CENTER RATING. FORK EXTENSIONS MUST NOT EXCEED 150% ORIGINAL FORK LENGTH.

P P R O V A	CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE [] As drawn [] As marked			
L	Signed:			_Date:
	Printed Name:			
	LEAD TIME WILL START UP	PON RECEI	PT OF SIGNED	APPROVAL DRAWING
ISTRIBUTOR'S NAME: P.O.# Y				
				ж W.O.# Х
RAW	^{n by:} C.CLEMENS	DATE: 7/8	5/16	^{SALES:} X
EFERENCE: X SCALE: 1:				FILE NAME:
UOTE	ED LEAD TIME: X	QUOTE # X	1	08-007-367