APPROX WEIGHT: 170.35 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PAGE

DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!! *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 78" **USABLE LENGTH** 6 1/8"±1/8" 7 3/8" 93 1/8" FORK EXTENSION MATERIAL **OVERALL LENGTH** THICKNESS IS 5/16" 39 5/16' Ø 5/8" 1/2"-(25/16")0 5 1/2" CENTER OF GRAVITY -USABLE STANDARD FEATURES **WIDTH** SPECIAL FEATURES **MODEL NUMBER IS FE-5-90-RS** DIMENSION TOLERANCE ± 1/4" **OVERALL WIDTH IS 6 1/8"** NONE I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS **OVERALL WIDTH W/LOOP IS 7 3/8"** REPRESENTED SATISFIES DESIGN AND DIMENSION **USABLE WIDTH IS 5 1/2'** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION **OVERALL LENGTH IS 93 1/8" USABLE LENGTH IS 78"** COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS **OVERALL HEIGHT IS 4 1/16"** R UNITS REQUIRING APPROVAL DRAWINGS OR FITS 5" WIDE x 2" MAX. THICKNESS FORK 0 MODIFIED ARE NON-RETURNABLE SOLID STEEL CONSTRUCTION ٧ [] As marked [] As drawn TOUGH BAKED IN POWDER COATED YELLOW FINISH APPROX. WEIGHT / LOST LOAD = 170.35 LBS. PER PAIR Signed: Date: MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED **Printed Name:** FORK EXTENSIONS DO NOT INCREASE THE LOAD LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING CENTER OF EXISTING FORK TRUCK. DISTRIBUTOR'S NAME: NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK MANUFACTURER'S GUIDELINES VESTIL MANUFACTURING W.O.# DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL DATE: 7/<u>8/16</u> SALES: X EXCEED FORK TRUCK MANUFACTURER'S LOAD **C.CLEMENS** CENTER RATING. reference: X SCALE: 1:14 FILE NAME: FORK EXTENSIONS MUST NOT EXCEED 150% ORIGINAL FORK LENGTH. QUOTED LEAD TIME: X QUOTE # 08-007-377 Χ