APPROX WEIGHT: lbs. FLOOR BRAKE SIDE MOUNT RIGHT - FL-LK-SMR-SS-R *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 4 1/2" $\emptyset 1.5/8'$ 2 29/32" Ø 13/32" x 13/16" SLOTS 4-PLACES 6 1/2" **SHOWN** 18" FULLY **EXTENDED EXTENDED** 15 3/4" FULLY WITH FLOOR LOCK RETRACTED **RETRACTED** MOUNT WITH THE BOTTOM PAD ABOUT 1 1/4" FROM FLOOR 12 1/8" **EXTENDED** 3 7/8" A LIGHT SPRAY LUBRICANT CAN BE USED TO HELP FLOOR LOCK MOVE MORE FREELY - 8 5/16" Ø3 1/2' STANDARD FEATURES DIMENSION TOLERANCE ± 1/2" MODEL NUMBER IS FL-LK-SMR-SS-R [] **OVERALL WIDTH IS 8 5/16"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION **OVERALL LENGTH IS3 31/32"** Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Ρ **OVERALL HEIGHT IS 18" EXTENDED** CONFIRM PRODUCT AND INSTALLATION Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE FOOT PAD3 1/2" R AND LOCAL REGULATIONS AND STANDARDS **MOUNTING HEIGHT IS 11 7/8"** 0 UNITS REQUIRING APPROVAL DRAWINGS OR DISTANCE FROM CENTER OF LOWER MODIFIED ARE NON-RETURNABLE HOLES TO PAD (FULLY EXTENDED) IS 12 1/8" [] As marked Α [] As drawn Signed: Date: SPECIAL FEATURES MOUNTING HEIGHT Printed Name: NONE (FROM CENTER OF 11 7/8" **SHOWN** LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING LOWER HOLES TO FLOOR) **RETRACTED** DISTRIBUTOR'S NAME: VESTIL MANUFACTURING W.O.# DRAWN BY: LAS SALES: X 6/11/2013 reference: X FILE NAME: **FLOOR** SCALE: 1:6

QUOTED LEAD TIME: Y

16-007-366

QUOTE #