## L-SHAPED MOLDED DOCK BUMPER - L-1818-4

DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\*
ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON





## STANDARD FEATURES

MODEL NUMBER IS L-1818-4
OVERALL LENGTH IS 18"
OVERALL HEIGHT IS 18"
OVERALL PROTECTION IS 4"
HOLE CENTERS ARE 9 1/2"
COUNTER SUNK HOLES FOR Ø 1" ANCHOR BOLTS
RESISTANT TO: ABRASION, FRICTION,
IMPACT DAMAGE, WEAR, CORROSION
AND WEATHER DAMAGE
CAN BE USED INDOOR OR OUTDOOR
APPROXIMATE WEIGHT IS 32 LBS

## SPECIAL FEATURES

NONE

## DIMENSION TOLERANCE ± 1/4"

		A P P R O V A	REPRESE REQUIREM CO COMPLIA AND L <b>UNITS RI</b>	ENTED SATI MENTS. I AL INFIRM PRO INCE WITH OCAL REC <b>EQUIRIN</b>	SFIES DE: SO ACK DDUCT A ALL APP BULATION G APPI ARE NO	ND INSTALLA LICABLE FED NS AND STAN ROVAL DR DN-RETUR	MENSION MY DUTY TO ATION ERAL, STATE IDARDS. AWINGS OR NABLE	
			Signed:				_Date:	
			Printed Nan	ne:				_
				L START UP	ON RECEI		APPROVAL DRAWI	ING
	RNAL USE ONLY	DISTRIB	BUTOR'S NAME:				P.O.# X	
PROJE	CT SIGN OFF	VE	ESTIL MAI	NUFAC	TURIN	IG	W.O.# _	
SALES		DRAW	/NI RV·		DATE:		X SALES: , ,	
ENG.			TAW		9/1	4/2016	Х	
FAB.		REFERE	X			SCALE: N/A	FILE NAME:	
OWER		QUOTE	ED LEAD TIME: X		QUOTE #		L-1818-4	