STANDARD SLOPE LADDER, 12-STEP, GRIP STRUT - LAD-PW-26-12-G APPROX WEIGHT: 266.20 lbs.

Does not include weight of power or packaging!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 23 9/16' 156" 120" 10" TYP. DIMENSION TOLERANCE ± 1/4" Ø 4' REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO STANDARD FEATURES 87 5/8' CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE MODEL NUMBER IS LAD-PW-26-12-G Ρ AND LOCAL REGULATIONS AND STANDARDS. NOTE OVERALL WIDTH IS 33 9/16" Ρ UNITS REQUIRING APPROVAL DRAWINGS OR SOME ASSEMBLY REQUIRED USABLE WIDTH IS 23 9/16" R MODIFIED ARE NON-RETURNABLE **OVERALL LENGTH IS 87 5/8"** TOOL TRAY SOLD SEPARATELY 0 **USABLE LENGTH IS 82 11/16"** [ ] As drawn [ ] As marked **OVERALL HEIGHT IS 156"** PLATFORM HEIGHT IS 120" Signed: Date: STEP TYPE IS GRIP STRUT SPECIAL FEATURES LEAD TIME WILL START UPON RECEIPT CLIMB ANGLE IS 58° OF SIGNED APPROVAL DRAWING

STEP DEPTH IS 7" PLATFORM DEPTH IS 14"

NONE

TOUGH BAKED IN POWDER COATED BLUE FINISH BOTTOM STEP IS TOUGH BAKED IN POWDER COATED YELLOW FINISH MAX CAPACITY IS 350 LBS

FRONT WHEEL IS SWIVEL. SIZE IS Ø 3" REAR WHEEL IS RIGID, SIZE IS Ø 4"

DISTRIBUTOR'S NAME: VESTIL MANUFACTURING

W.O.# X SALES: X

DRAWN BY: B.NOTHNAGEL REFERENCE: X

DATE: 9/15/2015 SCALE: 1:36 FILE NAME:

Quoted lead time:  $_{
m Y}$ QUOTE # Χ

44-007-482