APPROX WEIGHT: 1214.14 lbs. PORTABLE SCISSOR TABLE- PST-4848-4-47 DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ***ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE** DIMENSION TOLERANCE ± 1/2" TABLE HEIGHT TOLERANCE ± 1/2" DECK FLATNESS ± 1/4" 0 0 ۰ 48 3/8" 30" 45" 42" 0 80 3/4" FLOOR LOCK 17 3/16" 48 3/8" 8 3/16" 12V DC HYDRAULIC POWER UNIT ELECTRIC TOEGUARDS RAISE & LOWER BUTTONS ARE IN (STOPS TABLE FROM TOP OF POWER UNIT COWERING IF BUMPED) WITH ON-BOARD CHARGER MEETS OSHA 1910.212 & BATTERY CHARGE INDICATOR 47" ADJUSTABLE UPWARD TRAVEL LIMIT SWITCH **RAISED** 41 9/16" 12" **LOWERED**

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

 \emptyset 8" X 3" PHENOLIC

RIGID CASTERS

STANDARD FEATURES

MODEL NUMBER IS PST-4848-4-47

CAPACITY: 4,000 LBS.

PLATFORM WIDTH: 48 3/8"

PLATFORM LENGTH: 48 3/8"

PLATFORM LOWERED HEIGHT: 12"

PLATFORM RAISED HEIGHT: 47"

OVERALL WIDTH: 48 3/8"

OVERALL LENGTH: 80 3/4" **GROUND CLEARANCE: 2 3/4"**

CASTERS: TWO Ø8" X 3" PHENOLIC SWIVEL TWO Ø8" X 3" PHENOLIC RIGID

12V DC POWER UNIT W/ ON-BOARD CHARGER & BATTERY CHARGE INDICATOR

DURABLE LIQUID PAINT BLUE FINISH

SPECIAL FEATURES NONE

APPROVA	REPRESENT REQUIREMEN CONF COMPLIANC AND LOC UNITS REC MOD	ED SATISFIES DES TS. I ALSO ACKN IRM PRODUCT AI CE WITH ALL APPL CAL REGULATION UIRING APPR IFIED ARE NO	THAT THE PRODUCT AS IGN AND DIMENSION NOWLEDGE MY DUTY TO ND INSTALLATION LICABLE FEDERAL, STATE IS AND STANDARDS. ROVAL DRAWINGS OR N-RETURNABLE [] As marked
L	Signed:		Date:
	Printed Name: LEAD TIME WILL S		PT OF SIGNED APPROVAL DRAWIN

Ø 8" X 3" PHENOLIC

SWIVEL CASTERS

LEAD TIME WILL START UP	UN RECEIPT OF S	IGNED APPI	ROVAL DRAWIN
istributor's name:		P.O.#	[‡] X
VESTIL MANUFAC	W.O.	# X	
RAWN BY: CRA	DATE: 12/18/20)23 SALE	^
eference: X	SCALI	E: 1:18 ^{FILE 1}	
UOTED LEAD TIME: X	QUOTE # X	01-	-007-531