APPROX WEIGHT: 19.12 lbs. **RACK GUARD WITH RUBBER BUMPER INSERT - RUD-36** *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON \emptyset 5/16" 3 3/8" 3 PLACES 1 1/2" 18" **RUBBER BUMPER** HARDWARE = THREE - 1/4 - 20 UNC x 4" LG BOLTS THREE - 1/4 FLAT WASHERS THREE - 1/4 - 20 UNC NUTS 34 1/2" 36" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION P STANDARD FEATURES COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE P AND LOCAL REGULATIONS AND STANDARDS. MODEL NUMBER: RUD-36 R ALL SPECIAL UNITS ARE NON-RETURNABLE **OVERALL LENGTH: 36"** 0 [] As drawn [] As marked **OVERALL WIDTH: 3 3/8"** V **OVERALL DEPTH: 4 7/8"** Α Signed: Date: **USABLE WIDTH: 3 1/8"** LEAD TIME WILL START UPON RECEIPT USABLE DEPTH: 4 3/4" OF SIGNED APPROVAL DRAWING MATERIAL THICKNESS: 10 GAGE (.1345") P.O.# X POWDER COATED: SAFETY YELLOW DISTRIBUTOR'S NAME: W.O.# X INCLUDES RUBBER BUMPER VESTIL MANUFACTURING INCLUDES HARDWARE TO ATTACH DRAWN BY: T. MOORE SALES: X **GUARD TO RACK** 08/26/09 reference: X 4 7/8"

SPECIAL FEATURES

NONE

FILE NAME:

23-007-325

SCALE: 1:5

QUOTE #

Χ

Quoted lead time: $_{f Y}$