DC POWERED HYDRAULIC SCISSOR LIFT TABLE - SCTAB-1000-2040-DC APPROX WEIGHT: 284.96 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON DECK TOLERANCE ±1/2" TABLE HEIGHT TOLERANCES ±1/2" 51 9/16" 20 3/8 DECK FLATNESS ±1/4" ELECTRIC TOEGUARDS 40 3/8" (STOP TABLE FROM LOWERING IF BUMPED) MEETS OSHA 1910.212 STANDARD: **12V DC HYDRAULIC POWER UNIT RAISED AND LOWERED BUTTONS** 32" ARE ON TOP OF POWER UNIT RAISED WITH ON BOARD CHARGER HEIGHT AND HAND CONTROL. 8" -LOWERED HEIGHT UPPER TRAVEL 20 1/2 LIMIT SWITCH STANDARD FEATURES SPECIAL FEATURES **DIMENSION TOLERANCE ± 1/4"** MODEL NUMBER IS SCTAB-1000-2040-DC NONE I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION DECK WIDTH IS 20 3/8" Α REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO DECK LENGTH IS 40 3/8" CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. UNITS REQUIRING APPROVAL DRAWINGS OR Ρ **RAISED HEIGHT IS 32"** Ρ R LOWERED HEIGHT IS 8" Ο TABLE CAPACITY (EVENLY DISTRIBUTED) MODIFIED ARE NON-RETURNABLE V MAX CAPACITY IS 1,000 LBS [] As drawn [] As marked Α CONTROL IS HANDHELD 2 BUTTON. NEMA 4 PENDANT WITH MINIMUM 8' USABLE COIL CORD Date: Signed: SAFETY MAINTENANCE PROPS, DISPLACEMENT Printed Name: STYLE CYLINDERS INSTALLED ROD DOWN LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING EMERGENCY SAFETY STOP HYDRAULIC FUSES DISTRIBUTOR'S NAME: <u>Р.О.</u># Х UPPER TRAVEL LIMIT SWITCH ELECTRIC PINCH POINT GUARD VESTIL MANUFACTURING W.O.# Х DURABLE LIQUID PAINT BLUE FINISH DRAWN BY: CRA DATE: 10/<u>11/2017</u> SALES: X REFERENCE: X SCALE: 1:12 FILE NAME: QUOTED LEAD TIME: 🖌 QUOTF # 01-007-363

Х