

ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE
ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



SALES
ENG.
FAB.
POWER

MODEL #: SNM15-62-FF-27
CAPACITY: 1500 lbs
LOWERED HEIGHT: 2" LIFT HEIGHT: 62"
LIFT MOTOR: DC 2.0KW/24V
DRIVE MOTOR: 0.4KW/24V
ELECTROMAGNETIC BRAKE
BATTERY: 2 x 12V/80Ah
CHARGER: 24V/8amp (GEN2 MINI-(2) 4amp BANKS)
TURNING RADIUS: 88 5/8" (R2250mm)
DISPLACEMENT OF GEAR PUMP: 1.2 ml/r
TRAVEL SPEED WITH LOAD: 1.24 m/h
TRAVEL SPEED W/O LOAD: 1.86 m/h
STABILIZER WHEEL: Ø3x1 13/32"
DRIVE WHEEL: Ø10 x 3" FRONT WHEEL: Ø3-1/8 x 3-3/8"
OVERALL MAST HEIGHT: 78"
FIXED FORKS OVER FIXED LEGS
SAFETY SHEILD
SINGLE MAST
HANDLE: CH-2

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

SNM15-62-FF-27