## APPROX WEIGHT: 2821 lbs. TRUCK ACTUATED DOCKLEVELER- SU-1000-SCB \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 5"x5"x1/4" PADS WITH 6" 3" x 3" x 1/4" ANGLE WITH ANCHOR MIN. (BY OTHERS) ANCHORS (BY OTHERS) 12" LIP HS CHECKER PLATE 4" WELDS EVERY 8" **REAR CURB BUMPER-**1/4" HS CHECKER PLATE \*\*SEE APPROVAL DRAWING OF CORRESPONDING CURB ANGLE SET FOR MORE DETAILED CURB ANGLE DIAGONALS SPECIFICATIONS\*\* PIT LENGTH MUST BE EQUAL **PLAN VIEW** CARRIAGE BOXED SIX INCH CHANNEL 7 1/2" 7 1/2" SIDE VIEW PIT WIDTH 11" 11" CLEAR CLEAR TOP FRONT-PLEASE CIRCLE SPECIFICATIONS: 50" DOCK HEIGHT RECOMMENDED 1" NEW (PIT) CONSTRUCTION SLOPE STANDARD FEATURES **EXISTING** (PIT) CONSTRUCTION MODEL NUMBER: SU-1000-SCB **FRONT VIEW** PIT WIDTH: 74" PIT LENGTH: 104 1/2" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS PIT DEPTH: 48" REPRESENTED SATISFIES DESIGN AND DIMENSION CAPACITY (GROSS ROLLING LOAD): 20,000 LBS. REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α CONFIRM PRODUCT AND INSTALLATION VERTICAL SERVICE RANGE: 12" ABOVE/ 8" BELOW Ρ COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ AND LOCAL REGULATIONS AND STANDARDS. ALL STRUCTURAL STEEL CONSTRUCTION WELDING MEETS AWS. R ANY MODIFIED UNITS ARE NON-RETURNABLE DESIGN, ENGINEERING, AND FABRICATION COMPLIES WITH OSHA & ANSI MH30.1 0 [ ] As drawn [ ] As marked V WARNING: CHECK APPLICABLE STATE AND LOCAL CODES FOR YOUR AREA!! Α Signed: Date: \*\*SINGLE AXLE CAPACITY NOT TO EXCEED 70% OF LOAD CAPACITY Printed Name: DISTRIBUTOR'S NAME: FOR INTERNAL USE ONLY PROJECT SIGN OFF SPECIAL FEATURES VESTIL MANUFACTURING W.O.# **SALES** NONE DRAWN BY:

ENG. FAB. **POWER** 

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING SALES: X TJM 02/27/12 reference: X FILE NAME: SCALE: NTS QUOTED LEAD TIME: Y QUOTE # 07-007-036 Χ