ELECTRIC HYDRAULIC TRASH CAN DUMPER - TCD-M-48-AC *** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 46 1/16"[.] 20" MIN 77" MAX STANDARD FEATURES MODEL NUMBER: TCD-M-48-AC USABLE CHUTE WIDTH: 20" MIN TO 27" MAX **USAGE CHUTE LENGTH: 27 1/8" OVERALL LENGTH: 75 5/8"** OVERALL WIDTH: 46 1/16" OVERALL HEIGHT: 64 11/16" **OVERALL ROTATED HEIGHT: 113 15/16"** MAXIMUM ROTATED ANGLE: 45° DUMP HEIGHT: 48 7/8" WORKS WITH MODEL# TH-32/64/95 **UNIFORM CAPACITY IS 400 LBS** CASTERS: FRONT: 8" X 2" GFN SWIVEL REAR: 8" X 2" GFN RIGID TWO ADJUSTABLE FLOOR LOCKS INTERNAL POWER UNIT: 115 V AC SINGLE PHASE CONTROL IS HANDHELD, 2 BUTTON, NEMA 4 PENDANT WITH MINIMUM 8' USABLE 113 15/16" 8" X 2" COIL CORD **SWIVEL CASTERS** FRAME: DURABLE LIQUID PAINT BLUE FINISH CHUTE: TOUGH BAKED IN POWDER COATED YELLOW FINISH 64 11/16" /8" 48 7 39 SPECIAL FEATURES NONE DIMENSION TOLERANCE ± 1/4" 8" X 2" -75 5/8"· A P P , THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. RIGID CASTERS DISTRIBUTOR'S NAME: P.O.# χ UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-R **VESTIL MANUFACTURING** W.O.# X **RETURNABLE** 0 [] As drawn DRAWN BY: SJA [] As marked DATE: 7/2<u>8/2016</u> ٧ SALES: X Date: Signed: reference: X Α SCALE: 1:32 FILE NAME: Printed Name: QUOTED LEAD TIME: Y QUOTF # 34-007-015-001 LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING