## **ELECTRIC HYDRAULIC TRASH CAN DUMPER - TCD-M-48-DC**

APPROX WEIGHT: 557.58 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

<u> 46 1/16"</u> **−** 

## STANDARD FEATURES

MODEL NUMBER: TCD-M-48-DC USABLE CHUTE WIDTH: 20" MIN TO 27" MA USAGE CHUTE LENGTH: 27 1/8" OVERALL LENGTH: 75 5/8" OVERALL WIDTH: 46 1/16" OVERALL HEIGHT: 64 11/16" OVERALL ROTATED HEIGHT: 113 15/16" MAXIMUM ROTATED ANGLE: 45° DUMP HEIGHT: 48 7/8" WORKS WITH MODEL# TH-32/64/95 UNIFORM CAPACITY IS 400 LBS CASTERS:

FRONT: 8" X 2" GFN SWIVEL REAR: 8" X 2" GFN RIGID TWO ADJUSTABLE FLOOR LOCKS INTERNAL POWER UNIT: 12 V DC WITH ON-BOARD CHARGER CONTROL IS HANDHELD, 2 BUTTON, NEMA PENDANT WITH MINIMUM 8' USABLE COIL CORD

FRAME: DURABLE LIQUID PAINT BLUE FINISH CHUTE: TOUGH BAKED IN POWDER COATED YELLOW FINISH

## SPECIAL FEATURES NONE

27" MAX	20" MIN 27" MAX	
5/16"	27 1/8"	
ITH I, NEMA 4 SABLE	113 15/16"	
UE FINISH COATED		45°
39 1/2"	64 11/16"	

闦

## DIMENSION TOLERANCE ± 1/4"

A P	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.	8" X 2" RIGID75 5/8"75 5/8"	
P	UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-		Ρ.Ο.# χ
R	<b>RETURNABLE</b> [ ] As drawn [ ] As marked	VESTIL MANUFACTURING	<sup>W.O.#</sup> X
v	Signed: Date:	DRAWN BY: SJA DATE: 7/28/2016	sales: X
A		<sup>REFERENCE:</sup> χ SCALE: 1:36	FILE NAME:
-	Printed Name: LEAD TIME WILL START LIPON RECEIPT OF SIGNED APPROVAL DRAWING	QUOTED LEAD TIME: X QUOTE #	34-007-015

뗿