## **ELECTRIC HYDRAULIC TRASH CAN DUMPER - TCD-M-60-AC** APPROX WEIGHT: 636.13 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON <del>-4</del>6 1/16"-STANDARD FEATURES 20" MIN 27" MAX MODEL NUMBER: TCD-M-60-AC USABLE CHUTE WIDTH: 20" MIN TO 27" MAX **USAGE CHUTE LENGTH: 27 1/8" OVERALL LENGTH: 75 5/8"** OVERALL WIDTH: 46 1/16" **OVERALL HEIGHT: 77 9/16"** OVERALL ROTATED HEIGHT: 134 13/16" MAXIMUM ROTATED ANGLE: 45° DUMP HEIGHT: 60 1/2" WORKS WITH MODEL# TH-32/64/95 27 **UNIFORM CAPACITY IS 400 LBS** CASTERS: FRONT: 8" X 2" GFN SWIVEL REAR: 8" X 2" GFN RIGID TWO ADJUSTABLE FLOOR LOCKS INTERNAL POWER UNIT: 115 V AC SINGLE PHASE 134 13/16" CONTROL IS HANDHELD, 2 BUTTON, NEMA 4 PENDANT WITH MINIMUM 8' USABLE COIL CORD FRAME: DURABLE LIQUID PAINT BLUE FINISH CHUTE: TOUGH BAKED IN POWDER COATED YELLOW FINISH 65 13/16" 60 77 9'/16" SPECIAL FEATURES NONE -75 5/8" 8" X 2" RIGID CASTERS 8" X 2" SWIVEL

		_	CASTERS
A	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENT. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE		
PΠ	FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.	DISTRIBUTOR'S NAME:	Ρ.Ο.# χ
R	UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON- RETURNABLE		W.O.# X
O	[ ] As drawn [ ] As marked	DRAWN BY: SJA DATE: 7/28/2016	SALES: X
Α	Signed:Date:	REFERENCE: X SCALE: 1:32	FILE NAME:
	Printed Name:	QUOTED LEAD TIME: V QUOTE #	34-007-029-001
	LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING	Х	32, 32,