
# SINGLE SCISSOR LIFT & TILT TABLE - UNI-4048-4

APPROX WEIGHT: 639 lbs.

DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

\*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



### STANDARD FEATURES

MODEL NUMBER IS: UNI-4048-4 CAPACITY: 4,000 LBS. EVENLY DISTRIBUTED SEQUENCE 1:

RAISED HEIGHT: 14 3/4", TILT ANGLE 35° **OVERALL HEIGHT: 42"** 

SEQUENCE 2:

RAISED HEIGHT 11 3/4", TILT ANGLE: 40° **OVERALL HEIGHT 42 1/4"** 

LEVEL HEIGHT: 8"

DECK SIZE: 40" W X 48" L WITH 12" LIP

INTEGRAL MAINTENCE LOCK

ADJUSTABLE UPWARD TRAVEL LIMIT SWITCH UNIT MUST BE LAGGED TO THE FLOOR

**DURABLE LIQUID PAINT BLUE FINISH** 

## SPECIAL FEATURES

NONE

#### PLEASE CIRCLE SPECIFICATIONS:

POWER	AC		*DC			AIR/OIL		
MOTOR VOLTAGE			15 2	08	2	30 4	60	
DEDICATED CIRCUIT REQUIRED								
MOTOR PHASE		SINGLE			THREE			
CONTROL		HAND			<del>*FOOT</del>			
~ ALL BATTERY CHARGERS ARE 115V AC ~								
BATTERY CHI	RG. RE		MOTE_		40	<del>ON-BOARD</del>		
CHRG. INDIC	. INDICATOR			YES			-NO	
* AVAILABLE AT ADDITIONAL COST								

Α

Ρ

Ρ

R

0

V

Α

**Printed Name:** 

## DIMENSION TOLERANCE ± 1/4"

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

#### ANY MODIFIED UNITS ARE NON-RETURNABLE [ ] As drawn [ ] As marked

Signed: Date:

LEAD TIME WILL START UPO	ON RECEIF	'I OF SIGNED I	APPROVAL DRAWING
DISTRIBUTOR'S NAME:			P.O.# X
VESTIL MANUFAC	W.O.# X		
DRAWN BY: MTS	3/20/2016		SALES: X
reference: X		SCALE: 1:18	FILE NAME:
QUOTED LEAD TIME: Y	QUOTE #		03-007-014