## APPROX WEIGHT: 2756 lbs. ZERO LIFT & TILT TABLE - ZLTT-5272-2-48 \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON DECK TOLERANCES ± 1/2" TABLE HEIGHT TOLERANCES ± 1/2" DECK FLATNESS ± 1/4" **BOLT-ON USABLE LENGTH SECONDARY** 71 1/2" LOADING/UNLOAD (ENTRY) SIDE **SHROUD** WITH SAFETY TOE GUARD 20 1/4 **USABLE WIDTH OPERATOR** 52" SIDE **MAXIMUM** LEVEL HEIGHT 48" 1/2 **OVERALL WIDTH HOSE & CORD EXIT** 83 3/4 77 1/4" FRAME THIS END SAFETY SHROUD (4) ANCHORING COVERS PINCH POINTS STANDARD FEATURES **DIMENSION TOLERANCE ± 1/4"** LOCATIONS ON I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS MODEL NUMBER IS ZLTT-5272-2-48 **FRAME** REPRESENTED SATISFIES DESIGN AND DIMENSION **USABLE WIDTH IS 52"** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE **USABLE LENGTH IS 71 1/2"** CAPACITY IS 2,000 LBS (EVENLY DISTRIBUTED) Ρ LOWERED HEIGHT IS 1/2" AND LOCAL REGULATIONS AND STANDARDS R UNITS REQUIRING APPROVAL DRAWINGS OR MAXIMUM LEVEL HEIGHT IS 48" 0 REMOTE POWER UNIT 24 1/2" x 22 1/2" x 7 1/2" (L x W x H) WITH 8' HOSE & CABLE MODIFIED ARE NON-RETURNABLE MAXIMUM TILT ANGLE IS 45° [ ] As marked [ ] As drawn OVERALL WIDTH IS 77 1/4" **OVERALL LENGTH IS 83 3/4"** Signed: Date: CONTROL IS HANDHELD, 4 BUTTON, NEMA 4 **Printed Name:** PENDANT WITH MINIMUM 8' USABLE COIL CORD LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME: P.O.# ,, PLEASE CIRCLE SPECIFICATIONS: DURABLE LIQUID PAINT BLUE FINISH **EXTERNAL POWER UNIT POWER** AC VESTIL MANUFACTURING W.O.# SPECIAL FEATURES MOTOR VOLTAGE 115 208 DRAWN BY: KGH SALES: X **NONE** 1/22/2019 DEDICATED CIRCUIT REQUIRED 60Hz reference: X SCALE: 1:30 FILE NAME: MOTOR PHASE **THRFF** QUOTED LEAD TIME: X QUOTE # 04-007-034 **CONTROL HAND** Χ