Carriage mount lift master boom

Standard Features:

• Unique design converts fork trucks into overhead lifting cranes.

 Connected and secured to a new or existing fork truck with a Class II carriage mount.

- Each unit includes two lifting hooks.
- Comes with an infinitely adjustable locking screw.
- Available in 4,000 and 6,000 lb capacities.
- Durable steel construction.
- Tough baked-in powder-coat finish.





RALL	UNIFORM	WEIGHT (LB)
IGITI	CAPACITI	(LD)
75/11	4.000 II.	075

Model: LM-CM2-EBT-4

MODEL NUMBER DESCRIPTION WIDTH EXTENDED LENGTH HEIGHT C	CAPACITY (LB)	HT CAPACITY (LB)	(LB)
LM-CM2-EBT-4 Carriage Mount Class II 12" 145%" 27%" 4,	,000 lbs. 375	8" 4,000 lbs. 375	375
LM-CM2-EBT-6 Carriage Mount Class II 12" 145%" 27%" 6,	,000 lbs. 409	6,000 lbs. 409	409

hydraulic telescoping boom

Standard Features:

 Powered by either the fork truck hydraulics or 12V DC battery.

- Each unit includes two lifting hooks.
- Boom can be extended/retracted while loaded.
- Useable fork pockets are 7½"w x 2½"H and are on 24" centers.
- Includes a 36" safety restraint.
- Durable steel construction.
- Tough baked-in powder-coat finish.



MODEL NUMBER	POWER	FORK POCKET CENTER	OVERALL EXTENDED LENGTH	OVERALL HEIGHT	UNIFORM CAPACITY	WEIGHT (LB)
LM-1T-8-24-HBE-TP	Fork Truck Hydraulics	24"	144¾"	24½"	8,000 lbs. (2,000 movable)	714
LM-1T-8-24-HBE-DC	12V DC Powered	24"	144¾"	24½"	8,000 lbs. (2,000 movable)	858



Vestil Manufacturing Corporation Larissa Flora - Sales Representative

2999 North Wayne Street, P.O. Box 570 Angola, Indiana 46703, USA Phone: (260) 624-4341 Fax: (260) 665-1339

E-Mail: larissa@vestil.com Web: www.vestil.com