

# INFLATABLE DUNNAGE BAGS



## Standard Features:

- Minimizes product shifting and damage in transit.
- 2-ply construction consists of a polypropylene weave outer bag.
- Outer bag protects a polyethylene inner bag.
- Can be filled with standard shop air.
- Stores flat when empty.
- Recommended one time use per bag.

Model BAG-4836-L1  
Shown With BAG-L-IG



MODEL NUMBER	SIZE (W x L)	PRESSURE SEAL (PSI)	MAXIMUM WORKING PRESSURE (PSI)	AMERICAN ASSOCIATION OF RAILROAD LEVEL (AAR)	WEIGHT (LBS)
<b>INFLATABLE DUNNAGE BAGS</b>					
BAG-4836-L1	48" x 36"	2.9	8	1	3
BAG-4836-L3	48" x 36"	8	25	3	3
BAG-4884-L1	48" x 84"	2.9	8	1	3
BAG-4884-L3	48" x 84"	8	25	3	3

MODEL NUMBER	DESCRIPTION	AIR INLET THREAD NPT FEMALE (IN)	WEIGHT (LBS)
<b>INFLATION VALVE &amp; GUN</b>			
BAG-L-IG	INFLATION GUN FOR BAGS L1 & L3	1/4"	2

**Often used for rail, vessel, and intermodal shipments!**



**Vestil Manufacturing Corporation**  
**Larissa Flora - Sales Representative**

2999 North Wayne Street, P.O. Box 570  
Angola, Indiana 46703, USA

Phone: (260) 624-4341 Fax: (260) 665-1339  
E-Mail: [larissa@vestil.com](mailto:larissa@vestil.com) Web: [www.vestil.com](http://www.vestil.com)