

Counter-Balanced Powered Drive Lifts

*** Eliminates outriggers ***



*** Tight turning radius ***

Ideal for die handling, machine feeding, and loading & unloading trucks!

Model Number	Fork Size (W x L)	Lowered Height	Raised Height	Capacity (0" – 62")	Capacity (62" – 118")
S-CB-62	6-3/8" to 23-5/8" x 30"	1-3/16"	62"	1,100 lb.	---
S-CB-118	6-3/8" to 23-5/8" x 30"	1-3/16"	118"	1,100 lb.	500 lb.
S-2CB-118	8-3/8" to 23-1/4" x 36-1/4"	2"	118"	2,000 lb.	1,000 lb.
S-2CB-30	Optional 30" long forks (Only for model S-2CB-118)				
S-2CB-42	Optional 42" long forks (Only for model S-2CB-118)				
AGM-UPG-2-12V	AGM battery upgrade (2x 12V) Purchase with new unit				

Standard Features:

- Electromagnetic brake with automatic dead-man feature
- S-CB units have a turning radius of 45"
- S-2CB units have a turning radius of 55"
- Thumb wheel throttle offers infinite forward & reverse speeds
- 78" mast height will go through a standard doorway
- Ergonomic tiller head assembly has fingertip switches
- Adjustable forks for lifting multiple pallet sizes
- (2) 12V, 75-85 AH lead acid deep cycle batteries
- 24V DC drive and lift motor
- Rugged steel construction with lifting capacity up to 2,000 pounds
- Battery charger
- Battery level gauge
- Horn is included standard

Features powered drive and powered lift



Vestil Manufacturing Corporation
Joshua Sheets - Director of Marketing

2999 North Wayne Street, P.O. Box 570
 Angola, Indiana 46703, USA
 Phone: (260) 624-4330 Fax: (260) 665-1339
 E-Mail: josh@vestil.com Web: www.vestil.com